

Econo-Lift ® Dumbwaiter Systems
Fully UL Certified to ASME A17.1 &A17.5
UL File # SA32120 USA & Canada CSA B44

The most economical highest quality dumb waiter on the market

A floor or wall mounted drive system with a remote controller that includes Honeywell EMI interlocks.

The Econo-Lift ® Dumbwaiter from Elevation Innovation incorporates technology for ease of installation, usage, and maintenance. The system includes a UL certified relay logic controller. The electrical components are all pre-wired for ease of installation. Quick connectors are used to tie the Included EMI interlocks and level limit switch to the pre-wired call/send stations. An in use indicator is included on each call.

Standard Features:

- UL certified to ASME A17.1 and 17.5 codes—Canada CSA B44
- Operates under 36" kitchen cabinet
- Finished 9 ply birch cab with dovetailed joints
- Roll up Silver line gate system
- Cab configurations including front/back and 90 degree
- VFD (variable frequency drive) Relay logic dumbwaiter controller
- Call / Send stations with in use LED light
- Commercial grade aluminum rail / trolley system
- Safety devices including slack cable, final limit, and trolley brake
- Honeywell EMI interlock door safety devices
- 100 lb or 150 lb capacity included
- 30 fpm rated speed 33% faster than the competition
- Economical, reliable, simple to install cable drive
- Maintenance free 3 phase motor / gear assembly
- 115V 15 amp dumbwaiter operation
- Travel up to 27 feet and 3 stops
- Upper and lower emergency physical stops
- Warranty 5 year Limited Parts



Visit www.eilifts.com for all the information

Elevation Innovation







Elevation Innovation, Inc.

6060 Enterprise Dr. Suite A Diamond Springs, CA 95619

Phone: (877) 345-4387
Fax: (877) 285-3050
E-mail: info@eillifts.com
www.eilifts.com



Econo- Lift ® Dumbwaiter Systems

Fully UL Certified to USA - ASME A17.1 &A17.5 Canada CSA B44

Econo- Lift ® 100 lb. and 150 lb. Dumb Waiter Specifications

Deflection 100 lb. and 150 lb. dumbwaiter meet all codes per ANSI for cab deflection

DESIGN Floor loading or Counter height

CAR 20" x 20"x 30" (100 lb.) or 24" x 24" x 30" (150 lb.) Custom Size and Shape

SIZE Up to 10 ft cubed

MATERIAL 9 Ply Birch with two coats of clear finish, or Stainless Steel

OPENING One or two or three sides available.

CAPACITY 100 or 150 lbs

SPEED 30 fpm

POWER 115v (standard), 200v / 230V 50Hz operation available

POWER UNIT Floor mount, Wall mount above or below

WINDING DRUM High torque electric motor and completely enclosed worm gear, drums machined to

accommodate a single 1/8" 7 x 19 ANSI 304 improved plow stainless steel cable.

GUIDE RAIL Monorail type

CONTROLS Fully automatic allowing car to be sent or called from any floor. Terminal limit switch provided

for top final. Car stops automatically at landing levels. Door interlocks for hoist-way doors to prevent operation of the dumbwaiter unless doors are closed and to prevent opening of any

door except when the car is at the landing.

OPTIONAL removable adjustable shelves.

EQUIPTMENT

Dumbwaiter Kits Include:

- Guide rail & trolley assembly
- Motor / gear assembly
- Dumbwaiter cab
- VFD (variable frequency drive) dumb waiter controller
- Call stations with pre-wired harnesses
- Interlocks with pre-wired harnesses
- Limit switches with pre-wired harnesses
- Dumb waiter Assembly hardware
- Dumb waiter installation manual

Warranty:

5 year Limited Parts Warranty ~ 5 Year Drive Train Warranty.